

No.

3

HIGH PERFORMANCE

MADEPFL


PENETRATING WOOD SEALER



RTS

Daisy Dene • Inglewhite Road
Preston PR3 2EB
01772 780873
info@rtschemicals.co.uk

**WATER
REPEL**



Precautions

- Keep out of reach of children
- Do not get in eyes, on skin, or on clothing
- Wear protective gloves/protective clothing/eye protection/face protection
- IF SWALLOWED: Immediately call a poison centre/doctor
- IF ON SKIN: Wash with plenty of water/soap. If skin irritation or rash occurs get medical attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Get medical advice/attention if you feel unwell.

5L

No. 3 Water Repelling Impregnating Sealer for Wood

PROTECTS UNTREATED & RESTORED WOOD

Water Repel can be used on cladding, panelling, fencing, garden furniture and internal timber.

The micro technology formula binds with the surface, providing a hard wearing, invisible protective seal against water ingress, oil and stain penetration, as well as algae and moss growth on both horizontal and vertical surfaces.

APPLICATION:

**DO NOT DILUTE • USE ON A CLEAN DRY SURFACE
ALWAYS TEST ON A SMALL HIDDEN AREA TO ENSURE COMPATIBILITY**

- Shake container before use.
- Spray on. It may be worked in with a brush, long pile roller.
- Apply an even, saturated coat. Once the first coat starts to soak in, apply a further wet on wet coat within 15 minutes and before the first coat dries. This method gives deeper penetration into the substrate.
 - Do not allow the product to dry in between applications.
 - Avoid runs, drips or puddling by removing excess product from the surface. If the product has splashed onto adjacent surfaces it should be wiped off immediately with a soft damp cloth.
 - Clean tools and equipment immediately with soapy water.

Ready to use. Always test on a small hidden portion of the surface to be cleaned to check compatibility and performance before commencing with the whole area

DO NOT apply to hot surfaces or in strong direct sunlight.
DO NOT allow the product to dry in between applications.

Not suitable for non porous substrates.

Water repellent within 2 hours.